6-Section Clamp Carrier, 16.5' Wide



Spec Sheet

Quick Machinery Company 9730 Soda Bay Road, PMB 5032 Kelseyville, CA 95451 Phone: (707) 272-6719 Fax: (707) 277-0227

Machine Type:

Model Numbers:

Description:

Dimensions:

Weight:

Electrical Requirements:

Air Requirements:

Price (U.S. Dollars):

Please Contact:



CLAMP CARRIER

A-CCFP-16.5-06, B-CLMP-3.5-38, C-PCT1-16.5-06, D-PPF1-16.5, E-EMDR-06-16.5

16.5' width capacity, 6-section Clamp Carrier with (12) heavyduty, zinc-plated clamps per section (72 clamps total); clamps 38" opening, clamp jaws 3.5" high x 4.75" wide, with 1° inward draft.

Equipped with industrial-duty Pneumatic Clamp Tightener with air pressure regulator, Pneumatic overhead Panel Flattener with air pressure regulator and push-button Electric Motor Drive for Carrier rotation.

Standard features include heavy-duty frame with 3" diameter main shaft, 6" I-beam legs, foot levelers, coiled air lines, conduit-encased electrical wires, automatic air line oiler, high-quality urethane finish, toolbox with spare parts and tools.

20'W x 9'D x 9'H

Net: 6,600 lbs.; Shipping: 7,040 lbs. (compare!)

220V or 440V 3-ph; 7 amps @ 220V

21 cfm @ 90 psi (5 hp compressor)

\$23,924.00 f.o.b. Los Angeles, CA

Kevin Quick at Quick Machinery Company, 707-272-6719

6-Section Clamp Carrier, 16.5' Wide











Value Leader in Gluing Equipment

Ideal for Gluing Long Material

The QUICK 16.5' Wide, 6-Section Clamp Carrier is our widest 6section Clamp Carrier. It is ideal for gluing long material, such as handrail and mouldings.

Capable of producing 288 edge-glued panels per shift (6 panels per section x 6 sections x 8 hours), or 480 3" handrails per shift (10 handrails per section x 6 sections x 8 hours), the 16.5' Wide, 6-Section Clamp Carrier is ideal for shops that need to glue a large number of panels and/or material up to 16.5' long.

QUICK 6-Section Clamp Carriers are available in widths (maximum stock length capacities) of either 6.5', 8.5', 10.5' or 16.5'.

Sturdy Frame

Our 16.5' Wide, 6-Section Clamp Carrier has a very sturdy frame, with 3" main shaft (4 times as stiff torsionally as a 2" shaft) and 6" I-beam legs.

Pneumatic or Hydraulic Clamp Tightener

The Pneumatic Clamp Tightener (shown in the photos on this spec sheet) is a very fast, two-hand, impact-style wrench that really gets the job done in a hurry. It is actuated by an easy-press trigger. A Hydraulic Clamp Tightener is also available (at additional cost), that is powerful, uniform and quiet.

Panel Flattener and Electric Motor Drive

The Pneumatic Panel Flattener holds stock flat while the clamps are tightened. The Semi-Automatic Electric Motor Drive rotates the Carrier from section to section. It is smooth, quiet and efficient, and is operated by pressing four buttons on the machine's Control Box.

Super Heavy-Duty Clamps

Our industrial-duty, corrosion-resistant, zinc-plated clamps have 1" x 2" rails and huge 20mm (over 3/4") screws for super strength and durability. Each clamp weighs over 30 pounds!

The standard clamp jaws are 4-3/4" wide by 3-1/2" high, and each is angled inward one degree to keep stock held down securely in the clamps. Clamp jaws are available up to 6" high.

Clamps are available from 32" to 52" maximum opening.

Quick Machinery Company 9730 Soda Bay Road, PMB 5032, Kelseyville, CA 95451 Phone: (707) 272-6719, Fax: (707) 277-0227 E-mail: kevin@quickmachinerycompany.com

www.quickmachinerycompany.com